

873 G-Series Specifications

▲ 873 G-Series Key Specifications

873 G-series

Horsepower

73 hp

Rated Operating Capacity

2400 lbs

Tipping Load

4800 lbs

Operating Weight

7285 lbs

Travel Speed - High (1-Speed)

7.9 mph

Auxiliary High Flow

30 gpm

Length without Attachment

112.1 in

Overall Height

78 in

Height to Hinge Pin

124.3 in

Reach @ Maximum Height

40 in

▼ Engine

873 G-series

Horsepower

73 hp

▼ Performance

873 G-series

Rated Operating Capacity

2400 lbs

Tipping Load

4800 lbs

Operating Weight

7285 lbs

Travel Speed (2-speed option)

7.2 mph

Travel Speed - High (1-Speed)

7.9 mph

Tilt Breakout Force (SAE)

4700 lbf

▼ Capacities

873 G-series

Fuel Tank

25 gal

▼ Hydraulic System

873 G-series

System Relief @ Quick Couplers

3000 psi

Auxiliary High Flow

30 gpm

▼ Dimensions

873 G-series

Length with Standard Bucket

140.7 in

Length without Attachment

112.1 in

Width (with bucket)

74 in

Overall Height

78 in

Height to Hinge Pin

124.3 in

Reach @ Maximum Height

40 in

Standard Bucket

72 in

Terra Bucket

78 in

Standard Tires

12 x 16.5 10pr

Narrow Tires

12 x 16.5 10pr

Medium Duty Float Tires

12 x 16.5 10pr

▼ Instrumentation

873 G-series

Fuel Gauge

Gauge or Digital

Hourmeter

Gauge or Digital

Engine Coolant Temperature

BOSS System

Engine Air Filter

BOSS System

Engine Oil Pressure

BOSS System

▼ Features

873 G-series

Air Conditioning

Optional

Adjustable Seat

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Optional

Sound Option

Optional

Cab Heater

Optional

Operating Lights

Standard

Rear Window

Optional

Top and Rear Windows

Optional

Top Window

No

Lift-Arm Support

Standard

Seat Belt

Yes

Suspension Seat

Optional

Two Speed Travel

Optional

Deluxe Instrumentation

Optional

Engine Shutdown

Standard

Hydraulic Bucket Positioning

Optional

High Flow Option

Not Applicable

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Yes

Bob-Tach Attachment System

Standard